20 Watt Foldable Solar Panel

The 20 Watt Foldable Solar Panel is lightweight, durable and extremely portable.

The solar panels are mounted to weather resistant fabric that quickly folds for storage and unfolds for use.

Unmatched durability allows for use in the harshest environments and a panel that works even after a portion is damaged.

This compact panel fits easily into most backpacks and is the perfect accessory to provide power for a wide range of electronics.

The 20 Watt Foldable Solar Panel keeps you connected, powers your outdoor life, and helps you get more out of your outdoor adventures.

Tips For Best Use:

- Angle the solar panel toward the sun for best results.
- Always store in a cool dry environment.
- Not designed for use in the rain.
- Allow time to air dry before packing if the panel is wet.
- Routinely clean the solar panel to ensure best performance.



Benefits Include:

- Compact, lightweight, durable military tested (MIL-STD-810G).
- Easy to deploy and easy to store.
- Provides some power even in hazy and shaded environments.
- Light sensitive technology turns on early in the day and stays on later in the day.
- Multiple charging adapters to fit your needs and charge a wide range of devices.
- Designed, engineered and manufactured in the United States.

Foldable Charging Capabilities:

Devices:	10 Watt	20 Watt	30 Watt	60 Watt	90 Watt	120 Watt
Cell Phone	/	\	/	\	\	V
Tablet		V	/	V	/	V
Laptop			/	V	V	\
Battery (400 Wh)			V	V	V	/

Certifications:

- CF
- MIL-STD-810G
- . Dalla
- Berry Amendment Compliance



20 Watt Foldable Solar Panel

Electrical Characteristics

Rated Voltage at Pmax	15.4V
Rated Current at Pmax	1.2A
Open Circuit Voltage	21.9V
Short Circuit Current	1.5A

Physical Characteristics

Part Number	F16-1200
Folded Dimensions	12.7 x 7.5 x 1.5 inches 322.6 x 190.5 x 38.1 mm
Unfolded Dimensions	33.7 x 25.3 inches 856.0 x 642.6 mm
Weight	1.0 lbs 0.5 kg

Thermal Characteristics

Temperature Coefficient for Power	- 0.200 (%/C)		
Temperature Coefficient for Voltage	- 0.240 (%/C)		
Temperature Coefficient for Voc	- 0.300 (%/C)		
Temperature Coefficient for Isc	0.109 (%/C)		

25.3 inches

Standard Colors:

Stealth Black

33.7 inches

Custom Colors:

Camoflauge Digicam Desert Camo Khaki Woodland

IV Curve

Connectors

Standard Connector:

Delphi Weatherpack

Custom Connectors:

SAE

4.5 MM Barrel Anderson Powerpole



